

Mobile access steps with platform, single-sided access, with light-alloy treads and platform - 41972

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.



Product description

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.



Complies with EN 131-7

Product features

Base 0,82 m × 1,45 m	Coating natural	Connection Stile-Rung welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material Aluminium	Number of rungs, incl. platform 4	Pitch rung/tread 240 mm	Platform height 0.96 m	Platform length 800 mm
Platform width 600 mm	Standards EN 131-7	Transport dimensions 1.350 mm × 820 mm × 400 mm	Tread depth 200 mm	Type rung/tread serrated
Warranty 10 years	Weight 31.8 kg	Working height 2.95 m		