ZARGES

DATA SHEET

Mobile access steps with platform, single-sided access, with light-alloy treads and platform - 4197

Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.













PRODUCT DESCRIPTION

- Can be released safely and quickly for flexibility while working: comfortable ascent, four sprung castors for stability and easy handling.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

HINTS AND SPECIAL FEATURES

Double-sided handrail in accordance with EN 131-7 on access optional.
Complies with EN 131-7

PRODUCT FEATURES

Property	Value
Base	1,03 m × 2,17 m
Coating	natural

Property	Value
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	8
Pitch rung/tread	240 mm
Platform height	1.92 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	2.220 mm × 1.030 mm × 360 mm
Tread depth	200 mm
Type rung/tread	serrated
Warranty	10 years
Weight	45.6 kg
Working height	3.9 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 3



Handrail
SKU 41959



Pole barrier
SKU 41957



Tray
SKU 41967

SPARE PARTS 6



Castor, anti-static
SKU 803298



Push-on end cap
SKU 824409



Push-on end cap, antistatic
SKU 824475



Sprung castor for platform steps
SKU 802192



Sprung castor for platform steps
SKU 802193



User instructions label
SKU 800597

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/6/2026
Subject to change or error.