



# Mobile access steps with platform, double-sided access, with light-alloy treads and platform - 41983

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.



## Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

## Product features

Base	0,87 m × 2,06 m
Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	2 × 5
Number of treads	5
Pitch rung/tread	240 mm
Platform height	1.2 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.850 mm × 940 mm × 440 mm
Tread depth	200 mm
Type rung/tread	serrated
Warranty	10 years
Weight	41 kg
Working height	3.2 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 4/20/2026

Subject to change or error.