

## Variotec V - 42439

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

### Product description

- Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.
- Required working height can be set in increments corresponding to the rung spacing.
- Folds down to a space-saving compact size for transport.
- Functional, sturdy bolt hinges, bolted in place and easy to replace, order no. 42439 with aluminum lamellar joint.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance with EN131-1.
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Stiles made from extruded aluminium sections for maximum stability.
- High strength, non-twist rung/stile connections.



### Hints and special features

Ideal for use on steps/stairs as a result of rung-by-rung height adjustment on both sides.

### Product features



|                                  |                                    |
|----------------------------------|------------------------------------|
| Certification                    | TÜV-SÜD                            |
| Coating                          | natural                            |
| Connection Stile-Rung            | flanged                            |
| Dimensions, folded               | Missing translation                |
| Length as lean-to ladder         | 6.4 m                              |
| Length as trestle                | 3.09 m                             |
| Load capacity                    | max. 150 kg                        |
| Material                         | Aluminium                          |
| Number of rungs                  | 6                                  |
| Number of rungs                  | 4 × 6                              |
| Pitch rung/tread                 | 265 mm                             |
| Standards                        | EN 131-4                           |
| Stile depth                      | 60 mm                              |
| Stile depth                      | 70 mm                              |
| Stile depth                      | 60mm / 70mm                        |
| Transport dimensions             | 1.860 mm × approx. 780 mm × 210 mm |
| Tread depth                      | 30 mm                              |
| Type rung/tread                  | serrated                           |
| Warranty                         | 10 years                           |
| Weight                           | 22 kg                              |
| Working height as lean-to ladder | 7.1 m                              |
| Working height as stepladder     | 4.4 m                              |



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/17/2026

Subject to change or error.