


## Nova S - 42454

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

### Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep surfaces to stand on.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base	Coating	Connection Stile-Rung	Load capacity	Material
0,84 m x 0,44 m	natural	flanged	max. 150 kg	Aluminium



Number of rungs, incl. platform <b>4</b>	Overall base width <b>0.44 m</b>	Overall length <b>1.57 m</b>	Pitch rung/tread <b>216 mm</b>	Platform height <b>0.83 m</b>
Platform length <b>250 mm</b>	Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>	Stile depth <b>48 mm</b>
Stile depth steps/back stay <b>48mm / 48mm</b>	Transport dimensions <b>1.580 mm x 440 mm x 120 mm</b>	Tray <b>Plastic</b>	Tread depth <b>80 mm</b>	Type rung/tread <b>serrated</b>
Vertical ladder height <b>1.43 m</b>	Warranty <b>10 years</b>	Weight <b>5.8 kg</b>	Working height <b>2.85 m</b>	certification-mark-pf <b>TÜV-SÜD</b>