

Nova S - 42455

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep surfaces to stand on.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	Coating	Connection Stile-Rung	Load capacity	Material
0,99 m x 0,46 m	natural	flanged	max. 150 kg	Aluminium



Number of rungs, incl. platform 5	Overall base width 0.46 m	Overall length 1.8 m	Pitch rung/tread 216 mm	Platform height 1.05 m
Platform length 250 mm	Platform width 250 mm	Standards EN 131 professional	Stile depth 48 mm	Stile depth 48 mm
Stile depth steps/back stay 48mm / 48mm	Transport dimensions 1.810 mm x 470 mm x 120 mm	Tray Plastic	Tread depth 80 mm	Type rung/tread serrated
Vertical ladder height 1.65 m	Warranty 10 years	Weight 6.9 kg	Working height 3.05 m	certification-mark-pf TÜV-SÜD