

Nova S - 42458

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep surfaces to stand on.
- High-strength perlon belts prevent splay.
- Stable tread construction: robust, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|------------|------|---------|-----------------------|---------------|
| Anti splay | Base | Coating | Connection Stile-Rung | Load capacity |
|------------|------|---------|-----------------------|---------------|



| | | | | |
|---|---|---|---|-----------------------------------|
| Belt strap | 1,44 m x 0,54 m | natural | flanged | max. 150 kg |
| Material Aluminium | Number of rungs, incl. platform 8 | Overall base width 0.54 m | Overall length 2.49 m | Pitch rung/tread 216 mm |
| Platform height 1.7 m | Platform length 250 mm | Platform width 250 mm | Standards EN 131 professional | Stile depth 48 mm |
| Stile depth 48 mm | Stile depth steps/back stay 48mm / 48mm | Transport dimensions 2.500 mm x 540 mm x 120 mm | Tray Plastic | Tread depth 80 mm |
| Type rung/tread serrated | Vertical ladder height 2.29 m | Warranty 10 years | Weight 10.2 kg | Working height 3.7 m |
| certification-mark-pf TÜV-SÜD | | | | |