DATA SHEET

Nova B - 42463

A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.



PRODUCT DESCRIPTION

- A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.
- Stable access equipment for comfortable work at heights of up to 3.65 meters.
- Easy access up and down via sturdy 80-mm-deep treads.
- Firm positioning thanks to anti-slip plastic end caps.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Robust design: flanged step-rail connection with extruded aluminum profiles.
- Strong steel hinges.
- Enclosed rung profile and integrated guide tube.











HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Anti splay	Belt strap
Base	0,6 m × 0,44 m
Certification	TÜV-SÜD

Property	Value
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	3
Number of treads	2 × 3
Overall base width	0.44 m
Overall length	0.68 m
Pitch rung/tread	216 mm
Standards	EN 131 professional
Stile depth	48 mm
Transport dimensions	680 mm × 440 mm × 140 mm
Tread depth	80 mm
Type rung/tread	serrated
Vertical ladder height	0.64 m
Warranty	10 years
Weight	5.8 kg
Working height	2.2 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 6




Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Non-marking ladder end caps
SKU 40310



Pivot foot with rubber tread 100 x 55 mm
SKU 40997



Stile extension
SKU 40922



Toolbag
SKU 40300

SPARE PARTS 5



End cap
SKU 824150



Push-on end cap
SKU 824438



Splay prevention (belt strap)
SKU 800333



Stand-off
SKU 800320



User instructions label
SKU 800606

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/12/2026
Subject to change or error.