

Nova B - 42464

A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.

Product description

- A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.
- Stable access equipment for comfortable work at heights of up to 3.65 meters.
- Easy access up and down via sturdy 80-mm-deep treads.
- Firm positioning thanks to anti-slip plastic end caps.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Robust design: flanged step-rail connection with extruded aluminum profiles.
- Strong steel hinges.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|------------|-----------------|
| Anti splay | Belt strap |
| Base | 0,74 m × 0,47 m |



| | |
|------------------------|--------------------------|
| Certification | TÜV-SÜD |
| Coating | natural |
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |
| Material | Aluminium |
| Number of treads | 4 |
| Number of treads | 2 × 4 |
| Overall base width | 0.47 m |
| Overall length | 0.91 m |
| Pitch rung/tread | 216 mm |
| Standards | EN 131 professional |
| Stile depth | 48 mm |
| Transport dimensions | 920 mm × 470 mm × 140 mm |
| Tread depth | 80 mm |
| Type rung/tread | serrated |
| Vertical ladder height | 0.85 m |
| Warranty | 10 years |
| Weight | 8.1 kg |
| Working height | 2.4 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.