

Nova B - 42464

A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.

Product description

- A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.
- Stable access equipment for comfortable work at heights of up to 3.65 meters.
- Easy access up and down via sturdy 80-mm-deep treads.
- Firm positioning thanks to anti-slip plastic end caps.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Robust design: flanged step-rail connection with extruded aluminum profiles.
- Strong steel hinges.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	0,74 m × 0,47 m



Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	4
Number of treads	2 × 4
Overall base width	0.47 m
Overall length	0.91 m
Pitch rung/tread	216 mm
Standards	EN 131 professional
Stile depth	48 mm
Transport dimensions	920 mm × 470 mm × 140 mm
Tread depth	80 mm
Type rung/tread	serrated
Vertical ladder height	0.85 m
Warranty	10 years
Weight	8.1 kg
Working height	2.4 m

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/14/2026

Subject to change or error.