

## Strato DL - 44808

The inexpensive alternative for safe ascent and quick and flexible application.

### Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	8
Overall length	2.42 m



Pitch rung/tread 265 mm

Standards EN 131 professional

Stile depth 58 mm

Transport dimensions 2.420 mm × 360 mm × 60 mm

Tread depth 38 mm

Type rung/tread serrated

Warranty 10 years

Weight 4.3 kg

Working height 3.3 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/22/2026

Subject to change or error.