

# Strato DL - 44812

The inexpensive alternative for safe ascent and quick and flexible application.

## Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>	Number of rungs <b>12</b>
Overall length <b>3.54 m</b>	Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>68 mm</b>	Transport dimensions <b>3.540 mm × 360 mm × 70 mm</b>
Tread depth <b>38 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>7.9 kg</b>	Wide crosspiece <b>0.79 m</b>



ZARGES

Working height

**4.4 m**