

## Strato DL - 44816

The inexpensive alternative for safe ascent and quick and flexible application.

### Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	16
Overall length	4.67 m



Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	4.660 mm × 360 mm × 75 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	10.1 kg
Wide crosspiece	0.89 m
Working height	5.45 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 5/22/2026

Subject to change or error.