ZARGES

DATA SHEET

Everest 2DE - 44820

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.













PRODUCT DESCRIPTION

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- Both parts of the ladder can also be used separately as single ladders.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged

Property	Value
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	10
Number of rungs	2 × 10
Overall length, extended	4.93 m
Overall length, retracted	2.98 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	2.980 mm × 430 mm × 120 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	11.3 kg
Wide crosspiece	0.9 m
Working height	5.65 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 8



Ground spikes
SKU 40939



Gutter fastening
SKU 40999



Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Ladder stay / base stabiliser
SKU 40250



Stile extension for horizontal stabiliser bars
SKU 41987



Tension strap
SKU 40960



Toolbag
SKU 40300

SPARE PARTS 5



Horizontal stabiliser bar
SKU 800551



Plug-in end cap
SKU 824350



Plug-in end cap
SKU 824302



Push-on end cap
SKU 824242



User instructions label
SKU 800604

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.