

## Everest 2DE - 44822

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

### Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	420 mm



Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	12
Number of rungs	2 × 12
Overall length, extended	6.05 m
Overall length, retracted	3.54 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	3.540 mm × 430 mm × 135 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	15.4 kg
Wide crosspiece	1 m
Working height	6.8 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/15/2026

Subject to change or error.