

Everest 2DE - 44826

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Pitch rung/tread

16	2 × 16	8.29 m	4.66 m	265 mm
Standards EN 131 professional	Stile depth 85 mm	Transport dimensions 4.660 mm × 430 mm × 145 mm	Tread depth 38 mm	Type rung/tread serrated
Warranty 10 years	Weight 21.5 kg	Wide crosspiece 1.2 m	Working height 8.7 m	certification-mark-pf TÜV-SÜD