ZARGES

DATA SHEET

Everest 2DE - 44828

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.



PRODUCT DESCRIPTION

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged

Property	Value
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	18
Number of rungs	2 × 18
Overall length, extended	9.17 m
Overall length, retracted	5.23 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	5.230 mm × 430 mm × 145 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	23.9 kg
Wide crosspiece	1.2 m
Working height	9.8 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 7



Ground spikes
SKU 40939



Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Ladder stay / base stabiliser
SKU 40250



Stile extension for horizontal stabiliser bars
SKU 41989



Tension strap
SKU 40960



Toolbag
SKU 40300

SPARE PARTS 5



Horizontal stabiliser bar
SKU 800550



Plug-in end cap
SKU 824353



Plug-in end cap
SKU 824354



Push-on end cap
SKU 824243



User instructions label
SKU 800604

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.