

## Everest 2DE - 44828

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

### Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>420 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Pitch rung/tread

<b>18</b>	<b>2 × 18</b>	<b>9.17 m</b>	<b>5.23 m</b>	<b>265 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>85 mm</b>	Transport dimensions <b>5.230 mm × 430 mm × 145 mm</b>	Tread depth <b>38 mm</b>	Type rung/tread <b>serrated</b>
Warranty <b>10 years</b>	Weight <b>23.9 kg</b>	Wide crosspiece <b>1.2 m</b>	Working height <b>9.8 m</b>	certification-mark-pf <b>TÜV-SÜD</b>