




ZARGES

Skymaster DX - 44837

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Upper ladder can also be used separately as single ladders.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Ladder length as 3-part single ladder 4.4 m	Length as 2-part single ladder and as stepladder with push-on section 3.25 m	Load capacity max. 150 kg
---------------------------	---	---	--	-------------------------------------

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/12/2026

Subject to change or error.

1/2



Material	Number of rungs	Number of rungs	Overall length, retracted	Pitch rung/tread
Aluminium	7	3 × 7	2.14 m	265 mm
Standards	Stile depth	Transport dimensions	Tread depth	Type rung/tread
EN 131 professional	58 mm	2.130 mm × 500 mm × 170 mm	38 mm	serrated
Warranty	Weight	Wide crosspiece	Working height as 3-part single ladder	certification-mark-pf TÜV-SÜD
10 years	13.8 kg	0.8 m	5.2 m	