ZARGES

DATA SHEET

Skymaster DX - 44842

Functionality and flexibility with standard features and excellent price/performance.



PRODUCT DESCRIPTION

- Functionality and flexibility with standard features and excellent price/performance.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged

Property	Value
Ladder length as 3-part single ladder	8.3 m
Length as 2-part single ladder and as stepladder with push-on section	5.8 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	12
Number of rungs	3 × 12
Overall length, retracted	3.54 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	3.550 mm × 500 mm × 220 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	25.9 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	9 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 7



Ground spikes
SKU 40939



Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Ladder stay / base stabiliser
SKU 40250



Stile extension for horizontal stabiliser bars
SKU 41989



Tension strap
SKU 40960



Toolbag
SKU 40300

SPARE PARTS 7



Guide piece
SKU 800352



Horizontal stabiliser bar
SKU 800550



Plug-in end cap
SKU 824353



Plug-in end cap
SKU 824354



Push-on end cap
SKU 824243



Splay prevention (belt strap)
SKU 800330



User instructions label
SKU 800605

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/12/2026
Subject to change or error.