

Skymaster DX - 44842

Functionality and flexibility with standard features and excellent price/performance.

Product description

- Functionality and flexibility with standard features and excellent price/performance.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.

Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural





Connection Stile-Rung	flanged
Ladder length as 3-part single ladder	8.3 m
Length as 2-part single ladder and as stepladder with push-on section	5.8 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	12
Number of rungs	3 × 12
Overall length, retracted	3.54 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	3.550 mm × 500 mm × 220 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	25.9 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	9 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.