

Skymaster DX - 44842

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Ladder length as 3-part single ladder 8.3 m	Length as 2-part single ladder and as stepladder with push-on section 5.8 m	Load capacity max. 150 kg
Material	Number of rungs	Number of rungs	Overall length, retracted	Pitch rung/tread



Aluminium	12	3 × 12	3.54 m	265 mm
Standards EN 131 professional	Stile depth 85 mm	Transport dimensions 3.550 mm × 500 mm × 220 mm	Tread depth 38 mm	Type rung/tread serrated
Warranty 10 years	Weight 25.9 kg	Wide crosspiece 1.2 m	Working height as 3- part single ladder 9 m	certification-mark-pf TÜV-SÜD