

Everest 3DE - 44853

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium



Number of rungs	12
Number of rungs	3 × 12
Overall length, extended	8.33 m
Overall length, retracted	3.53 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	3.530 mm × 500 mm × 190 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	24.2 kg
Wide crosspiece	1.2 m
Working height	8.8 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/29/2026

Subject to change or error.