

Everest 3DE - 44853

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 12	Number of rungs 3 x 12	Overall length, extended 8.33 m	Overall length, retracted 3.53 m	Pitch rung/tread 265 mm



Standards EN 131 professional	Stile depth 85 mm	Transport dimensions 3.530 mm × 500 mm × 190 mm	Tread depth 38 mm	Type rung/tread serrated
Warranty 10 years	Weight 24.2 kg	Wide crosspiece 1.2 m	Working height 8.8 m	