

# Everest 3DE - 44854

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

## Product description

- Flexible, safe and inexpensive: the perfect solution for accessing great heights.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Upper ladder can also be used separately as single ladders for Order Nos. 44851-44852.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Overall width of bottom section: 490 mm.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>490 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs <b>14</b>	Number of rungs <b>3 × 14</b>	Overall length, extended <b>9.45 m</b>	Overall length, retracted <b>4.09 m</b>	Pitch rung/tread <b>265 mm</b>



Standards	Stile depth	Transport dimensions	Tread depth	Type rung/tread
EN 131 professional	85 mm	4.090 mm × 500 mm × 190 mm	38 mm	serrated
Warranty	Weight	Wide crosspiece	Working height	
10 years	36 kg	1.2 m	9.9 m	