ZARGES

DATA SHEET

Combimaster DX - 44868

The inexpensive alternative for universal use as a push-up ladder and stepladder.
















PRODUCT DESCRIPTION

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Base	1,64 m × 0,89 m
Certification	TÜV-SÜD
Coating	natural

Property	Value
Connection Stile-Rung	flanged
Length as trestle	2.25 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	8
Number of rungs	2 × 8
Overall length, extended	3.82 m
Overall length, retracted	2.4 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	2.400 mm × 420 mm × 120 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	10 kg
Wide crosspiece	0.89 m
Working height	4.9 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 7



End cap
SKU 824152



Guide piece
SKU 800352



Horizontal stabiliser bar
SKU 800551



Plug-in end cap
SKU 824350



Push-on end cap
SKU 824242



Splay prevention (belt strap)
SKU 800328



User instructions label
SKU 800594

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 10/31/2026
Subject to change or error.