



ZARGES

## Combimaster DX - 44868

The inexpensive alternative for universal use as a push-up ladder and stepladder.

### Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base <b>1,64 m × 0,89 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Length as trestle <b>2.25 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>8</b>	Number of rungs <b>2 × 8</b>	Overall length, extended <b>3.82 m</b>	Overall length, retracted <b>2.4 m</b>



Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
<b>265 mm</b>	<b>EN 131 professional</b>	<b>58 mm</b>	<b>2.400 mm × 420 mm × 120 mm</b>	<b>38 mm</b>
Type rung/tread	Warranty	Weight	Wide crosspiece	Working height
<b>serrated</b>	<b>10 years</b>	<b>10 kg</b>	<b>0.89 m</b>	<b>4.9 m</b>
certification-mark-pf				<b>TÜV-SÜD</b>