

Combimaster DX - 44868

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|--------------------------------|-----------------------------|---|---|---|
| Base 1,64 m × 0,89 m | Coating natural | Connection Stile-Rung flanged | Length as trestle 2.25 m | Load capacity max. 150 kg |
| Material Aluminium | Number of rungs 8 | Number of rungs 2 × 8 | Overall length, extended 3.82 m | Overall length, retracted 2.4 m |

| | | | | |
|------------------------------------|---|-----------------------------|---|--------------------------------|
| Pitch rung/tread 265 mm | Standards EN 131 professional | Stile depth 58 mm | Transport dimensions 2.400 mm × 420 mm × 120 mm | Tread depth 38 mm |
| Type rung/tread serrated | Warranty 10 years | Weight 10 kg | Wide crosspiece 0.89 m | Working height 4.9 m |