

Combimaster DX - 44870

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Length as trestle 2.81 m	Load capacity max. 150 kg	Material Aluminium
Number of rungs 10	Number of rungs 2 x 10	Overall length, extended 4.94 m	Overall length, retracted 2.98 m	Pitch rung/tread 265 mm



Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 2.970 mm × 430 mm × 120 mm	Tread depth 38 mm	Type rung/tread serrated
Warranty 10 years	Weight 12.3 kg	Wide crosspiece 0.9 m	Working height 5.7 m	certification-mark-pf TÜV-SÜD