

# Combimaster DX - 44872

The inexpensive alternative for universal use as a push-up ladder and stepladder.

## Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Length as trestle <b>3.33 m</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs <b>12</b>	Number of rungs <b>2 × 12</b>	Overall length, extended <b>6.06 m</b>	Overall length, retracted <b>3.54 m</b>	Pitch rung/tread <b>265 mm</b>



Standards	Stile depth	Transport dimensions	Tread depth	Type rung/tread
EN 131 professional	73 mm	3.530 mm × 430 mm × 130 mm	38 mm	serrated
Warranty	Weight	Wide crosspiece	Working height	
10 years	15.3 kg	1 m	6.8 m	