

Combimaster DX - 44872

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a push-up ladder and stepladder.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	natural
Connection Stile-Rung	flanged
Length as trestle	3.33 m
Load capacity	max. 150 kg
Material	Aluminium



Number of rungs	12
Number of rungs	2 × 12
Overall length, extended	6.06 m
Overall length, retracted	3.54 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	3.530 mm × 430 mm × 130 mm
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years
Weight	15.3 kg
Wide crosspiece	1 m
Working height	6.8 m
certification-mark-pf	TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/19/2026

Subject to change or error.