

# Y-Case and SanPack -

## 45055

Transport and storage container for military applications.

### Product description

- Casing joint welded throughout.
- Extra strong 1.5 mm sheet
- Sturdy base, edge and lid profile.
- Hinged lid with all-round seal.
- Sturdy cast stacking corners on lid and base.
- Stacking feet on the base with attachment bores on inside and outside.
- Watertight up to lower edge of the drop handle due to silicon seal inside on the base.
- Snap fasteners with protection against bursting open.
- Ergonomic & durable C. fasteners for at least 20,000 operating cycles.
- Lid loose in the case of B 40.1 Y, B 40.2 Y and B 40.4 Y.
- IP 54 protection class according to DIN EN 60 529 : 1992



### Hints and special features

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

UN approval for the transportation of hazardous



goods possible at additional charge.

## Product features

Internal dimensions L x W x H <b>794 mm × 572 mm × 220 mm</b>	Max. gross weight dangerous goods permission <b>46 kg</b>	Outside dimensions max. L x W x H <b>835 mm × 615 mm × 270 mm</b>	Version <b>B20.2 Y</b>	Volume <b>99 l</b>
Weight <b>11.4 kg</b>				