ZARGES

DATA SHEET

Y-Case and SanPack - 45055

Transport and storage container for military applications.

PRODUCT DESCRIPTION



- Casing joint welded throughout.
- Extra strong 1.5 mm sheet
- Sturdy base, edge and lid profile.
- Hinged lid with all-round seal.
- Sturdy cast-iron stacking corners on the lid
- Stacking feet on the base with attachment bores on inside and outside.
- Waterproof down to the bottom edge of the drop handle thanks to a silicone seal on the inside of the base.
- Snap fasteners with protection against bursting open.
- Ergonomic & durable C. fasteners for at least 20,000 operating cycles.
- Lid loose in the case of B 40.1 Y, B 40.2 Y and B 40.4 Y.
- IP 54 protection class according to DIN EN 60 529 : 1992



HINTS AND SPECIAL FEATURES

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.
UN approval for the transportation of hazardous goods possible at additional charge.

PRODUCT FEATURES

Property	Value
Internal dimensions L x W x H	794 mm × 572 mm × 220 mm
Max. gross weight dangerous goods permission	46 kg
Outside dimensions max. L x W x H	835 mm × 615 mm × 270 mm

Property	Value
Version	B20.2 Y
Volume	99 l
Weight	11.4 kg

ACCESSORIES AND SPARE PARTS

ACCESSORIES 1



Dangerous Goods Approval
SKU 926000

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/11/2026
Subject to change or error.