



Y-Case and SanPack -

45057

Transport and storage container for military applications.

Product description

- Casing joint welded throughout.
- Extra strong 1.5 mm sheet
- Sturdy base, edge and lid profile.
- Hinged lid with all-round seal.
- Sturdy cast-iron stacking corners on the lid
- Stacking feet on the base with attachment bores on inside and outside.
- Waterproof down to the bottom edge of the drop handle thanks to a silicone seal on the inside of the base.
- Snap fasteners with protection against bursting open.
- Ergonomic & durable C. fasteners for at least 20,000 operating cycles.
- Lid loose in the case of B 40.1 Y, B 40.2 Y and B 40.4 Y.
- IP 54 protection class according to DIN EN 60 529 : 1992



Hints and special features

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

UN approval for the transportation of hazardous

goods possible at additional charge.

Product features

| | |
|--|----------------------------|
| Internal dimensions L x W x H | 1.175 mm × 793 mm × 717 mm |
| Max. gross weight dangerous goods permission | 200 kg |
| Outside dimensions max. L x W x H | 1.215 mm × 833 mm × 761 mm |
| Version | B40.1 Y |
| Volume | 668 l |
| Weight | 25.7 kg |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/29/2026

Subject to change or error.