


# Aluminium shaft covers with cover trough - 47005

Shaft covers that can be walked or driven on, with customisable inner and outer surface.

## Product description

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapering section design, therefore easy to open. No sticking.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load with choice of surface: test force 125 kN (=12.5 t), only after cover trough has been filled by customer with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 60 mm (of which 40 mm covered with construction steel grating and 20 mm free area)



## Product features

|                                     |   |  |                                     |                                     |
|-------------------------------------|---|--|-------------------------------------|-------------------------------------|
| Design height<br><b>80 mm</b>       | Inside shaft length<br><b>635 mm</b>                        | Inside shaft size<br><b>635mm × 635mm</b>              | Inside shaft width<br><b>635 mm</b> | Material, cover<br><b>Aluminium</b> |
| Material, frame<br><b>Aluminium</b> | Outside dimensions max. L x W x H<br><b>775 mm × 775 mm</b> | Transport dimensions<br><b>770 mm × 770 mm × 70 mm</b> | Trough depth<br><b>60 mm</b>        |                                     |