

## AXIC-Y - 47809

Double lanyard with elastic arms according to EN 354:2010 and integrated energy absorber according to EN 355:2002. The integrated O-ring prevents the arms from twisting during use. The length is flexible and can be varied between 1.40 m and 1.80 m. The lanyard is optionally equipped with carabiners or rebar hooks.



### Product description

- Double lanyard according to EN 354:2010 with energy absorber according to EN 355:2002.
- Flexible length between 1.40 and 1.80 m.
- Equipped with carabiners or rebar hooks.
- Due to its round shape, the central RING eyelet allows optimal positioning to prevent twisting.
- Suitable for people up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- Suitable for sharp edges, RfU 11.074.

### Product features

Anchoring Carabiner	Aluminum rebar hook
Edge capable	Yes
Energy Absorber	Yes
Harness Carabiner	Aluminum snap carabiner
Length Range	1,4-1,8 m
Maximum Service Life	10 J
Maximum Weight of User	150 kg



Maximum length 1.8 m

Minimum length 1.4 m

Smart Check Yes

Standards EN 354, EN 355

Weight 1.8 kg

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 3/29/2026

Subject to change or error.