

AXIC-Y - 47861

Double lanyard with elastic arms in accordance with EN 354:2010 and an integrated energy absorber in accordance with EN 355:2002. The integrated O-ring prevents distortion of the arms during use. The length is adjustable and can be varied between 1.40 m and 1.80 m. The lanyard is available with either carabiners or rebar hooks.

Product description

- Double lanyard in accordance with EN 354:2010 with an energy absorber in accordance with EN 355:2002.
- Adjustable length between 1.40 and 1.80 m.
- Equipped with carabiners or rebar hooks.
- Thanks to its round shape, the central RING eyelet allows for optimal positioning to prevent distortion.
- Suitable for people weighing up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- Suitable for sharp edges, RfU 11.074.



Product features

Carabiner Anchor Point Page	Aluminum snap carabiner
Carabiner Full Body Harness Page	Twist-lock
Length Range	1,4-1,8 m
Maximum length	1.8 m
Maximum service life	10 J
Maximum user weight	150 kg



Minimum length	1.4 m
Smart Check	Yes
Standards	EN 354,EN 355
Suitable for edges	Yes
Weight	1.15 kg
energy absorber	Yes

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/27/2026

Subject to change or error.