DATA SHEET

Liberex - 47881

The reliable and safe descent and rescue device with high load capacity.









PRODUCT DESCRIPTION

- The Liberex descent and rescue device for self-rescue stands out with its high load capacity, robust design, and automatic braking system. It enables safe descents from heights of up to 500 m. Equipped with a 10.5 mm kernmantle rope, ZmartCheck for fast digital data access, and a QR code for easy access to inspection instructions – ideal for professional self-rescue and safe descent from great heights.
- ZmartCheck - provides quick access to security-relevant information.
- High load capacity of up to 280 kg, certified for two users.
- Maximum descent height of 500 m for greater flexibility.
- Descent speed 1 m/s.
- Equipped with eye bolts for controlled descent speed.
- Automatic, redundant braking system for full control.
- Kernmantle rope with a diameter of 10.5 mm for safe operation.
- Inspection interval every 10,000 meters or once per year.
- Equipped with a Tri-Lock carabiner for increased safety.
- Aluminum housing for high durability.
- Inspection instructions accessible via QR code – instantly available in digital format.
- Length: 20 m

HINTS AND SPECIAL FEATURES

EN 341-A

PRODUCT FEATURES

Property	Value
Carabiner Anchor Point Page	Tri-lock
Carabiner Full Body Harness Page	Tri-lock
Housing Material	Aluminium
Length	20 m
Material	10.5 mm kernmantel ropes
Maximum service life	10 J
Payload	280 kg
Standards	EN 341-A
Weight	5.5 kg

ACCESSORIES AND SPARE PARTS

SPARE PARTS 1



Liberex/Liberex+ Inspection/ Cleaning Kit
SKU 47929

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/22/2026
Subject to change or error.