

MultiTower S-PLUS 1T, 1,80

m - 52225

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

Product description

- The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Scaffold width: 0.75 m; scaffold length: 1.80 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

Product features



| | | | | |
|---------------------------------|--|---|---------------------------------|--|
| Claw type automatic | Height-adjustable castors: Yes | Overall height 2.65 m | Platform height 1.4 m | Platform length 1.8 m |
| Platform length 1.8 m | Platform size 0,6m x 1,8m | Platform width 0.6 m | Rung diameter 50 mm | Scaffolding class 3 (= 200 kg/m²) |
| Standards EN 1004-1 | Stile diameter 50 mm | Transport dimensions 2.100 mm x 900 mm x 400 mm | Warranty 10 years | Weight 95.2 kg |
| Wheel diameter 200 mm | Width scaffolding 0.75 m | Working height 3.4 m | | |