

MultiTower S-PLUS 1T, 1,80

m - 52295

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.



Product description

- The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.
- Scaffold width: 0.75 m; scaffold length: 1.80 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

Product features



Claw type automatic	Height-adjustable castors: Yes	Overall height 9.65 m	Platform height 8.4 m	Platform length 1.8 m
Platform length 1.8 m	Platform size 0,6m x 1,8m	Platform width 0.6 m	Rung diameter 50 mm	Scaffolding class 3 (= 200 kg/m²)
Standards EN 1004-1	Stile diameter 50 mm	Transport dimensions 2.100 mm x 900 mm x 1.100 mm	Warranty 10 years	Weight 247.8 kg
Wheel diameter 200 mm	Width scaffolding 0.75 m	Working height 10.4 m		