

MultiTower S-PLUS 1T, 2,50 m - 52306

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

Product description

- The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.
- Scaffolding width: 0.75 m; scaffolding length: 2.50 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

Product features

Claw type automatic	Height-adjustable castors: Yes	Overall height 10.45 m	Platform height 9.2 m	Platform length 2.5 m
Platform length 2.5 m	Platform size 0,6m × 2,5m	Platform width 0.6 m	Rung diameter 50 mm	Scaffolding class 3 (= 200 kg/m²)
Standards EN 1004-1	Stile diameter 50 mm	Transport dimensions 2.800 mm × 900 mm × 1.200 mm	Warranty 10 years	Weight 328.1 kg
Wheel diameter 200 mm	Width scaffolding 0.75 m	Working height 11.2 m		