

# MultiTower S-PLUS 2T, 1,80 m - 52435

Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.

## Product description

- Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights ranging from 3.40 m to a maximum of 13.20 m can be achieved using standard components.
- Scaffolding Group 3 (strength up to 200 kg/m<sup>2</sup>) in accordance with DIN EN 1004-1.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



## Hints and special features

By adding the relevant S-PLUS single parts, this safer configuration can also be retrofitted to standard mobile scaffold towers with triangular stabilisers.

## Product features



|                            |                              |
|----------------------------|------------------------------|
| Claw type                  | automatic                    |
| Height-adjustable castors: | Yes                          |
| Overall height             | 3.75 m                       |
| Platform height            | 2.5 m                        |
| Platform length            | 1.8 m                        |
| Platform length            | 1.8 m                        |
| Platform size              | 1,2m × 1,8m                  |
| Platform width             | 1.2 m                        |
| Rung diameter              | 50 mm                        |
| Scaffolding class          | 3 (= 200 kg/m <sup>2</sup> ) |
| Standards                  | EN 1004-1                    |
| Stile diameter             | 50 mm                        |
| Transport dimensions       | 2.100 mm × 1.500 mm × 500 mm |
| Warranty                   | 10 years                     |
| Weight                     | 140.7 kg                     |
| Wheel diameter             | 200 mm                       |
| Width scaffolding          | 1.35 m                       |
| Working height             | 4.5 m                        |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/13/2026

Subject to change or error.