

MultiTower S-PLUS 2T, 2,50 m - 52436

Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.

Product description

- Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Scaffolding width: 1.35 m; scaffolding length: 2.50 m.
- Working heights ranging from 3.40 m to a maximum of 13.20 m can be achieved using standard components.
- Scaffolding Group 3 (strength up to 200 kg/m²) in accordance with DIN EN 1004-1.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Hints and special features

By adding the relevant S-PLUS single parts, this safer configuration can also be retrofitted to standard mobile scaffold towers with triangular stabilisers.

Product features



Claw type	automatic
Height-adjustable castors:	Yes
Overall height	3.75 m
Platform height	2.5 m
Platform length	2.5 m
Platform length	2.5 m
Platform size	1,2m × 2,5m
Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m ²)
Stile diameter	50 mm
Transport dimensions	2.800 mm × 1.500 mm × 500 mm
Warranty	10 years
Weight	161.8 kg
Wheel diameter	200 mm
Width scaffolding	1.35 m
Working height	4.5 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.