


CompactMaster S-PLUS 2T

- 53221

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- Scaffolding width: 0.85 m or 1.45 m (lower section incl. hinges); Scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding Group 3 (strength up to 200 kg/m²) in accordance with DIN EN 1004-1.
- Standard casters: 150 mm swivel castors with height adjustment (order no. 42755) for precise height adjustment down to the millimeter.



Product features

Claw type	automatic
Height-adjustable castors:	Yes
Overall height	3.85 m
Platform height	2.6 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	1,2m × 1,8m



Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m ²)
Stile diameter	50 mm
Transport dimensions	0 mm0 mm0 mm
Warranty	10 years
Weight	161.4 kg
Wheel diameter	150 mm
Width scaffolding	1.45 m
Working height	4.6 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.