ZARGES

DATA SHEET

CompactMaster 1T - Basispaket - 53300

Reach greater heights quickly and safely: modularly extendable folding scaffold unit which folds to compact size for transport and is quickly erected and dismantled.









PRODUCT DESCRIPTION

- The base packs for expanding up to a working height of 13.55 m.
- Basic module folds together for rapid erection and dismantling.
- Minimum space requirement during transport and storage (dimensions when folded only 0.25 x 0.85 m).
- Scaffolding width: 0.85 m (to the outside edge of folding unit hinge); scaffolding length: 1.80 m.
- Can be extended up to a working height of 13.65 m, because the basic model already includes a platform with trapdoor.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 125 mm swivel castors (Order No. 42973) for millimetre-perfect level adjustment; can be replaced with height-adjustable 200 mm castors (Order No. 42917) for an additional charge.
- Standard castors for scaffold towers with a working height of up to 3.50 m: 125 mm swivel castors (order no. 42959) with brake.

PRODUCT FEATURES

Property	Value
Claw type	automatic
Height-adjustable castors:	No

Property	Value
Overall height	1.65 m
Platform height	0.95 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	0,6m × 1,8m
Platform width	0.6 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m²)
Stile diameter	50 mm
Transport dimensions	1.900 mm × approx. 950 mm × approx. 480 mm
Warranty	10 years
Weight	35.8 kg
Wheel diameter	125 mm
Width scaffolding	0.85 m
Working height	2.95 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 2



Automatic steel hinge
SKU 820688



Spring clip for scaffolding
SKU 800172

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/9/2026
Subject to change or error.