

## CompactMaster 2T -

### Basispaket - 53400

Reach greater heights quickly and safely: modularly extendable folding scaffold unit which folds to compact size for transport and is quickly erected and dismantled.

#### Product description

- The base packs for expanding up to a working height of 13.55 m.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights can be extended from 3.85 m to max. 13.65 m with standard parts.
- Can be extended up to a working height of 13.65 m, because the basic model already includes a platform with trapdoor.
- Small, practical and easy to use scaffold unit for interior and exterior work at low heights.
- Minimum space requirement during transport and storage (dimensions when folded only 0.25 x 0.85 m).
- Scaffolding category 3 (for loads of up to 200 kg/m<sup>2</sup>) according to DIN EN 1004, i.e. here with 404 kg.
- Standard castors: 125 mm with pin (no height adjustment) and rubber coating, for working heights of up to 6.55m.





## Product features

Claw type <b>automatic</b>	Fits through doorways <b>No</b>	Height-adjustable castors: <b>No</b>	Overall height <b>1.65 m</b>	Platform height <b>0.95 m</b>
Platform length <b>1.8 m</b>	Platform length <b>1.8 m</b>	Platform size <b>1,2m × 1,8m</b>	Platform width <b>1.2 m</b>	Rung diameter <b>50 mm</b>
Scaffolding class <b>3 (= 200 kg/m<sup>2</sup>)</b>	Stile diameter <b>50 mm</b>	Transport dimensions <b>0 mm × 0 mm × 0 mm</b>	Warranty <b>10 years</b>	Weight <b>52.8 kg</b>
Wheel diameter <b>125 mm</b>	Width scaffolding <b>1.45 m</b>	Working height <b>2.95 m</b>		