

CompactMaster 2T - Basispaket - 53400

Reach greater heights quickly and safely: modularly extendable folding scaffold unit which folds to compact size for transport and is quickly erected and dismantled.

Product description

- The base packs for expanding up to a working height of 13.55 m.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights can be extended from 3.85 m to max. 13.65 m with standard parts.
- Can be extended up to a working height of 13.65 m, because the basic model already includes a platform with trapdoor.
- Small, practical and easy to use scaffold unit for interior and exterior work at low heights.
- Minimum space requirement during transport and storage (dimensions when folded only 0.25 x 0.85 m).
- Scaffolding category 3 (for loads of up to 200 kg/m²) according to DIN EN 1004, i.e. here with 404 kg.
- Standard castors: 125 mm with pin (no height adjustment) and rubber coating, for working heights of up to 6.55m.



Product features



Claw type	automatic
Fits through doorways	No
Height-adjustable castors:	No
Overall height	1.65 m
Platform height	0.95 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	1,2m × 1,8m
Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m ²)
Stile diameter	50 mm
Transport dimensions	0 mm × 0 mm × 0 mm
Warranty	10 years
Weight	52.8 kg
Wheel diameter	125 mm
Width scaffolding	1.45 m
Working height	2.95 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.