ZARGES

DATA SHEET

CompactMaster 2T - Basispaket - 53400

Reach greater heights quickly and safely: modularly extendable folding scaffold unit which folds to compact size for transport and is quickly erected and dismantled.

PRODUCT DESCRIPTION

- The base packs for expanding up to a working height of 13.55 m.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights can be extended from 3.85 m to max. 13.65 m with standard parts.
- Can be extended up to a working height of 13.65 m, because the basic model already includes a platform with trapdoor.
- Small, practical and easy to use scaffold unit for interior and exterior work at low heights.
- Minimum space requirement during transport and storage (dimensions when folded only 0.25 x 0.85 m).
- Scaffolding category 3 (for loads of up to 200 kg/m²) according to DIN EN 1004, i.e. here with 404 kg.
- Standard castors: 125 mm with pin (no height adjustment) and rubber coating, for working heights of up to 6.55m.





PRODUCT FEATURES

Property	Value
Claw type	automatic
Fits through doorways	No

Property	Value
Height-adjustable castors:	No
Overall height	1.65 m
Platform height	0.95 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	1,2m × 1,8m
Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m²)
Stile diameter	50 mm
Transport dimensions	0 mm × 0 mm × 0 mm
Warranty	10 years
Weight	52.8 kg
Wheel diameter	125 mm
Width scaffolding	1.45 m
Working height	2.95 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 2



Automatic steel hinge
SKU 820688



Spring clip for scaffolding
SKU 800172

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/9/2026
Subject to change or error.