

CompactMaster 2T -

Basispaket - 53400

Reach greater heights quickly and safely: modularly extendable folding scaffold unit which folds to compact size for transport and is quickly erected and dismantled.

Product description

- The base packs for expanding up to a working height of 13.55 m.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights can be extended from 3.85 m to max. 13.65 m with standard parts.
- Can be extended up to a working height of 13.65 m, because the basic model already includes a platform with trapdoor.
- Small, practical and easy to use scaffold unit for interior and exterior work at low heights.
- Minimum space requirement during transport and storage (dimensions when folded only 0.25 x 0.85 m).
- Scaffolding category 3 (for loads of up to 200 kg/m²) according to DIN EN 1004, i.e. here with 404 kg.
- Standard castors: 125 mm with pin (no height adjustment) and rubber coating, for working heights of up to 6.55m.



Product features

Claw type automatic	Fits through doorways No	Height-adjustable castors: No	Overall height 1.65 m	Platform height 0.95 m
Platform length 1.8 m	Platform length 1.8 m	Platform size 1,2m × 1,8m	Platform width 1.2 m	Rung diameter 50 mm
Scaffolding class 3 (= 200 kg/m²)	Stile diameter 50 mm	Transport dimensions 0 mm × 0 mm × 0 mm	Warranty 10 years	Weight 52.8 kg
Wheel diameter 125 mm	Width scaffolding 1.45 m	Working height 2.95 m		