

PaxTower 1T - 53510

Product description

- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.



Product features

Claw type automatic	Fits through doorways Yes	Height-adjustable castors: No	Overall height 1.65 m	Platform height 0.55 m
Platform length 1.8 m	Platform length 1.8 m	Platform size 0,6m x 1,8m	Platform width 0.6 m	Rung diameter 45 mm



Scaffolding class 3 (= 200 kg/m²)	Standards EN 1004-1	Stile diameter 45 mm	Transport dimensions 1.950 mm × 750 mm × 350 mm	Warranty 10 years
Weight 29.1 kg	Wheel diameter 125 mm	Width scaffolding 0.72 m	Working height 2.55 m	